

TYPE

TOLERIE

www.rtsystem.ch
info@rtsystem.ch

Fabrication









Tôle galvanisé

Utilisation

Conception d'un réseau pour véhiculer de l'air

Pose

Par emboîtement, étanché par silicone ou scotch



Ø mm	80	100	125	150	160	180	200	225	250
SR Tube spiro 2m	8.20/m	8.70/m	10.00/m	12.40/m	13.10/m	14.60/m	16.30/m	18.40/m	20.20/m
NP Manchon mâle	5.10	5.10	5.30	5.60	5.80	6.50	6.60	7.10	8.70
MF Manchon fem.	5.10	5.10	5.30	5.60	5.80	6.50	6.60	7.10	8.70
IL Piquage plat	6.50	5.30	5.80	6.50	6.80	7.30	7.80	8.70	9.90
BG45 Coude 45°	12.40	12.40	15.00	20.70	21.80	26.40	29.10	39.30	45.60
BG90 Coude 90°	15.60	15.60	19.70	28.60	29.40	38.90	43.00	60.20	71.40
EP Fond	7.10	7.10	8.00	9.40	9.40	11.60	12.60	17.90	17.90
PS Piquage/rond	9.00	9.00	11.40	14.30	15.00	18.00	19.70	27.20	27.90
TC Té	25.30	26.40	29.40	40.30	40.30	55.80	55.80	83.10	83.10
RC Réduction	/	9.70	11.40	12.10	12.10	13.90	15.60	18.70	21.80
DS Clapet manuel	38.40	39.60	41.50	43.20	44.00	46.10	46.80	58.10	59.20
YV 45° Culotte 45°	/	111.00	115.00	121.00	123.00	130.00	143.00	153.40	167.00

Autres dimensions sur demandes